T1S R1W DUCHESNE COUNTY MONUMENT SURVEY RECORD SEC 18 | SEC 17 5/8"X24" REBAR WITH A 2½" DIA. ALUMINUM DUCHESNE SEC 19 | SEC 20 COUNTY MONUMENT AT 1/4 CORNER 00.10 U.S.B.&M. 2642.01 N-545 NAIL AND WASHER IN IN LEFT SIDE OF RR TIE FENCE POST N 66.56.00" M NAIL AND SURVEY CAP IN LEFT SIDE OF FENCE CORNER POST 17 × 58° 17' 25' "X" CHISELED IN CONCRETE WATER 33.32 VALVE COLLAR X 83°15'21" 40.80 S 63'10'20" W NAIL AND WASHER IN IN LEFT SIDE OF CORNER FENCE POST CORNER FENCE POST 00.07,22," - X - Q NORTH NOTE: THE BASIS OF BEARINGS IS GEODETIC NORTH DERIVED FROM G.P.S. OBSERVATIONS AT A CONTROL POINT (SECTION CORNER) LOCATED AT LAT. 40"23"20.57790"N AND LONG. 110"01"46.98583"W USING THE UTAH STATE G.P.S. VIRTUAL REFERENCE STATION CONTROL NETWORK MAINTAINED AND OPERATED BY THE AUTOMATED GEOGRAPHIC REFERENCE CENTER SCALE: 1"=30' 5/8"X24" REBAR WITH A 2½" ALUMINUM DUCHESNE COUNTY MONUMENT AT 1/4 CORNER 0' 30'

DESCRIPTION OF CORNER EVIDENCE FOUND

FOUND MONUMENT SPIKE (HARROW TOOTH) AT POSITION OF SECTION CORNER

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THE CORNER

SET A 5/8"X24" REBAR WITH A 2½"
ALUMINUM DUCHESNE COUNTY MONUMENT
AT THE POSITION OF THE SECTION CORNER
AFTER ROAD CONSTRUCTION



STATE PLANE COORDINATE DATA

(U.S. SURVEY FEET)
NAD83 UTAH CENTRAL ZONE
N: 7313808.479
E: 2049947.222
NAVD88 EL: 5694.19

LATITUDE: 40°23'20.57790" N **LONGITUDE:** 110°01'46.98583" W

ELLIPSOID HEIGHT: 5639.46'

(GEOID 03 CONUS)

PUBLIC LAND SURVEY SYSTEM GCDB ID NO.

UT300010S0010W0_200400

CERTIFICATION

I <u>Jerry D. Allred</u>, Professional Land Surveyor, State of Utah, do hereby certify that I have performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve same

Date <u>28 FEB 2018</u>

Jerry D. Allred, Professional Land Surveyor Certificate No. 148951 Duchesne County Surveyor

